THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- extension-of-type-approval
- refusal-of-type-approval
- withdrawal-of-type-approval

of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4*94/20*0355*00

Reason for extension:

SECTION I

0.1	Make (trade name of manufacturer)	:	Bosal
0.2.	Type and general commercial description(s)	:	017813
0.3.	Means of identification of type if marked on the component	:	Approval number
0.3.1.	Location of the marking	:	on type plate
0.5.	Name and address of manufacturer	:	Bosal Postbus 168 4920 AD MADE
0.7.	In the case of components and separate technical units, location and method of affixing of the EEC approval mark	:	on type plate
0.8.	Name(s) and address(es) of assembly plants	:	see information document (Annex III), item 0.8



Type-approval number : e4*94/20*0355*00

SECTION II

1. Additional information (where applicable)

: see Appendix I

2. Technical sevice responsible for

carrying out the tests

: Rijksdienst v/h Wegverkeer

F.E. Plancius

Testbaan|Centrum
Talingweg 76
8218 NX Lelystad

3. Date of test report

: 03-06-1996

4. Number of test report

: TCL-94/20-112/96

5. Remarks (if any)

: see Appendix I

6. Place

: Zoetermeer

7. Date

18. JULI 199

8. Signature

9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request:

- Application form relating to Annex III and annexed drawings
- Drawings and instructions for attachment
- Fitting instructions
- Testreport, as mentioned in item 4.

551-3218

Appendix I

to EEC type-approval certificate No : e4*94/20*0355*00 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

1. Additional information

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which the device is designed or restricted

: see fitting instructions

1.3. Maximum D-value : 11,79 kN

1.4. Maximum vertical load S at the coupling point : 75 kg

1.5. Maximum load U at the fifth wheel coupling point : -- ton

1.6. Maximum V-value : -- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

: see fitting instructions

1.8. Information on the fitting of special towing brackets or mounting plates

: see fitting instructions

5. Remarks

: The fitting of the towbar on the vehicle must be checked according annex I nr.5.10, according the presciptions mentionend in annex VII

