

### THE NETHERLANDS



### EEC TYPE-APPROVAL CERTIFICATE

# Communication concerning the:

- type-approval
- extension-of-type-approval
- refusal-of-type-approval
- withdrawal-of-type-approval

of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4\*94/20\*0969\*00

Reason for extension:

## SECTION I

0.1	Make (trade name of manufacturer)	:	Bosal
0.2.	Type and general commercial description(s)	:	022641

0.3. Means of identification of type if

marked on the component : Approval number

0.3.1. Location of the marking : on type plate

0.5. Name and address of manufacturer : Bosal

Postbus 168 4920 AD MADE

0.7. In the case of components and separate technical units, location and method of affixing of the EEC approval mark

: on type plate

0.8. Name(s) and address(es) of assembly plants : see information

document

(Annex III), item 0.8



## SECTION II

 Additional information (where applicable)

: see Appendix I

2. Technical service responsible for

carrying out the tests

: RDW

Testbaan | Centrum Talingweg 76 8218 NX Lelystad

3. Date of test report

: 22-12-1997

4. Number of test report

: TCL-94/20-824/97

5. Remarks (if any)

: see Appendix I

6. Place

: Zoetermeer

7. Date

18. MRT 1998

8. Signature

- RDW RDW liged with the competent authority
- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request:
  - Application form relating to Annex III and annexed drawings
  - Drawings and instructions for attachment
  - Fitting instructions
  - Testreport, as mentioned in item 4.

# Appendix I

# to EEC type-approval certificate No : e4\*94/20\*0969\*00 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

Additional information

1.1. Class of the type of coupling A50-X

1.2. Categories or types of vehicles for which the device is designed or restricted

see fitting instructions

1.3. Maximum D-value 6.82 kN

1.4. Maximum vertical load S at the coupling point

50 kg

1.5. Maximum load U at the fifth wheel coupling point

ton

1.6. Maximum V-value kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

see fitting instructions

1.8. Information on the fitting of special towing brackets or mounting plates

see fitting instructions

5. Remarks

The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I,

par.5.10.

