

THE NETHERLANDS

EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval

~~extension of type-approval~~- ~~refusal of type-approval~~- ~~withdrawal of type-approval~~

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number : e4\*94/20\*0018\*00

Reason for extension :


## SECTION I

- 0.1 Make (trade name of manufacturer) : BOSAL
- 0.2. Type and general commercial description(s) : 9012077
- 0.3. Means of identification of type  
marked on the component : Typeshield
- 0.3.1. Location of the marking : Typeshield on connectorsocket
- 0.5. Name and address of manufacturer : TOBO b.v.  
Postbus 168  
4920 AD MADE
- 0.7. In the case of components and separate  
technical units, location and method of  
affixing of the EEC approval mark : Typeshield
- 0.8. Name(s) and address(es) of assembly plants : See information  
document  
(annex III, item 0.8)



Type-approval number : e4\*94/20\*0018\*00

## SECTION II

1. Additional information  
(where applicable) : See appendix I
2. Technical service responsible for  
carrying out the tests : Rijksdienst v/h Wegverkeer  
Europaweg 202  
2711 ER Zoetermeer
3. Date of testreport : 06-03-1995
4. Number of testreport : TC-59/68-TRE-061/94
5. Remarks (if any) : See appendix I
6. Place : Zoetermeer
7. Date : 17. MRT 1995
8. Signature :   
J.D. Vecht
9. The index to the information package lodged with the competent authority that  
has granted type-approval, which may be obtained on request, is attached.
  - Application form relating to annex III and annexed drawings
  - Drawings and instructions for attachment
  - Fitting instructions
  - Test report as mentioned in item 4.

Appendix I  
to EEC type-approval certificate No : e4\*94/20\*0018\*00  
concerning the components type-approval of mechanical coupling devices with regard to  
Directive 94/20/EEC

1. Additional information
- 1.1. Class of the type of coupling : A50-X
- 1.2. Categories or types of vehicles for which the device is designed or restricted : M1, N1 Ford Transit Bestel--> 94  
(see fitting instructions)
- 1.3. Maximum D-value : 12,49 kN
- 1.4. Maximum vertical load S at the coupling point : 75 kg
- 1.5. Maximum load U at the fifth wheel coupling point : -- ton
- 1.6. Maximum V-value : -- kN
- 1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles : See fitting instructions
- 1.8. Information on the fitting of special towing brackets or mounting plates :
5. Remarks : The fitting of the towbar on the vehicle must be checked according annex I nr. 5.10, according the prescriptions mentioned in annex VII

